


Pendant stations



Hoist control: **P02 P03 HP03 DC30**



LIFTING EQUIPMENT

Characteristics:

- Bi-directional, mechanically interlocked
- IP 65 double insulation IEC/EN60529
- General and electrical data page 23
- Laser engraved symbols comply with EN60204-1, FEM 9.941
- Shock proof and heat resistant

PICTURE	LAYOUT	CONFIGURATION	CODE	CONTACT TYPE	WEIGHT [gr]
P02 KIT Available See pg. 18 Available in UL/CSA req.		SINGLE SPEED (* TILTING BUTTON 16A – 250Vac ½ HP)	P02.RM		230
		SINGLE SPEED	P02.1		230
			P02.2		250
			P02.4		250
		(* HIGH POWER CONTACTS DIRECT MOTOR CONTROL 1Kw 1ph	P02.CD		230
P02.D2				250	
P03 KIT Available See pg. 18 Available in UL/CSA req.		SINGLE SPEED	P03.1		440
			P03.2		450
			P03.3		460
			P03CD		460
		TWO SPEED	P03D2		460
HP03 Available in UL/CSA req.				SINGLE SPEED	HP03
		TWO SPEED			HP03.D2
DC30 				SINGLE SPEED (* Ith 25A EXTRA HIGH POWER CONTACTS BLOCK FOR DIRECT MOTOR CONTROL : 2.2kW 1ph / 4kW 3ph	DC30
	DC30.RG				600
	DC30.GE				600
	DC30D2				650